

PolyE 3000T Gloss

Media Type	Label	✓	Film Type	Polyethylene	✓
	Receipt			Polyolefin	
	Tag			Polypropylene	
	Wristband			Polyester	
Material Type	Paper			Polyimide	
	Synthetic	✓	Properties	Cold Temperature	
Printing Technology	Direct Thermal (no Ribbon Required)			Deep Freeze	
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
Adhesive Type	Permanent	✓		Ultra High Temperature	
	Removable			High Tack	
	No Adhesive		Chemical Resistance	-	
Finish	Matte		Environment	Indoor	✓
	Gloss	✓		Outdoor	✓

Additional Features

- Low cost, topcoated gloss polyethylene label
- Good adhesion on a variety of substrates
- Good flexibility and conformability for labelling curved surfaces
- Pure polyethylene facestock means it is environmentally-friendly and recyclable
- Good tear and water resistance properties
- BgVV approved for direct contact with dry, moist and non-fatty foodstuffs

Suggested Applications

- Labelling of HDPE bottles and cans e.g. toiletries and food packaging
- Work in progress labels
- Pallet labelling suitable for recycling with shrink-wrap
- Cost effective outdoor labelling for plants, garden and DIY products (approx. 9 months)
- Medium-life product and box labelling
- Shelf-edge labelling
- Gloss materials are not suitable for fanfold applications

Technical Specifications

	Description	Caliper
Facestock	Gloss white topcoated polyethylene film	100 microns
Adhesive	Permanent acrylic adhesive	20 microns
Liner	65gsm glassine liner	55 microns
	Total	175 microns \pm 10%

Recommended Zebra Printers: Desktop, mid-range and high-performance thermal printers

Recommended Zebra Ribbons: 4800, 5095

Minimum Application Temperature: 5°C
When the label is applied, the environment and surface should be above this temperature

Service Temperature Range: -10°C to 80°C
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

Recommended Storage Conditions: 1 year duration when stored at 15°C to 25°C, at 45% to 55% RH
Storage of product before use

Expected Life Span in Application: Indoor use, 1 year+
Outdoor use, up to 1 year
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order from the ZipShip price list or sample roll SAMPLE5730.